

Geniř Halka



MARKA:

FİYAT:

| Kod | Nominal Ölçü (mm) | Çalışma Yüğü (t) | Tost Yüğü (kN) | Kopma Yüğü (kN) | Ağırlık kg/nt |
|---------|----------------------|---------------------|-------------------|--------------------|------------------|
| Enorm K | 6 x 18 | 1,4 | 35,3 | 56,5 | 0,8 |
| Enorm K | 8 x 24 | 2,5 | 62,8 | 101 | 1,5 |
| Enorm K | 10 x 30 | 4 | 98,1 | 157 | 2,3 |
| Enorm K | 13 x 39 | 6,7 | 166 | 265 | 3,9 |
| Enorm K | 16 x 48 | 10 | 251 | 402 | 5,8 |
| Enorm K | 18 x 54 | 12,5 | 318 | 509 | 7,4 |
| Enorm K | 22 x 66 | 19 | 475 | 760 | 11 |
| Enorm K | 26 x 78 | 26,5 | 664 | 1060 | 15,9 |

Değişik zincir ısılarına göre izi verilen yük limitleri (EN- 818-6 standartlarına göre):

Allowed working loads (EN- 818-6) for different chain temperature

40 C bis + 200 C = 100%

200 C bis + 300 C = 90%

300 C bis + 400 C = 75 %

Once the Enorm - chain has cooled down to room temperature it can be again used to 100%

Once the Enorm - chain has cooled down to room temperature it can be again used to 100%